



西安禾盛达机械设备有限公司
Xi'an HSender Mechanical Equipment Co.,Ltd


Drilling tool COUPLING SLEEVE

Excellent rock drilling equipment supplier




Coupling

R25




| Length | | Diameter | |
|--------|-------------------------------|----------|--------------------------------|
| mm | inch | mm | inch |
| 150 | 5 ⁷ / ₈ | 33 | 1 ⁵ / ₁₆ |
| 160 | 6 ¹ / ₄ | 35 | 1 ³ / ₈ |

R32




| Length | | Diameter | |
|--------|--------------------------------|----------|---------------------------------|
| mm | inch | mm | inch |
| 150 | 5 ⁷ / ₈ | 44 | 1 ²³ / ₃₂ |
| 160 | 6 ⁵ / ₁₆ | 44 | 1 ²³ / ₃₂ |

R38



| Length | | Diameter | |
|--------|-------------------------------|----------|--------------------------------|
| mm | inch | mm | inch |
| 170 | 6 ³ / ₄ | 55 | 2 ⁵ / ₃₂ |
| 180 | 7 ¹ / ₈ | 55 | 2 ⁵ / ₃₂ |


T38



| Length | | Diameter | |
|--------|-------------------------------|----------|--------------------------------|
| mm | inch | mm | inch |
| 190 | 7 ¹ / ₂ | 52 | 2 ⁵ / ₁₆ |
| 190 | 7 ¹ / ₂ | 55 | 2 ⁵ / ₃₂ |
| 180 | 7 ¹ / ₂ | 55 | 2 ⁵ / ₃₂ |


Coupling

T45




| Length | | Diameter | |
|--------|-------|----------|---------|
| mm | inch | mm | inch |
| 210 | 8 1/4 | 63 | 2 15/32 |
| 210 | 8 1/4 | 66 | 2 15/32 |

T60




| Length | | Diameter | |
|--------|-------|----------|---------|
| mm | inch | mm | inch |
| 315 | 1 3/8 | 85 | 3 11/32 |

T51




| Length | | Diameter | |
|--------|-------|----------|---------|
| mm | inch | mm | inch |
| 225 | 8 7/8 | 71 | 2 51/64 |
| 225 | 8 7/8 | 76 | 3 |
| 255 | 10 | 72 | 2 27/32 |

Coupling R32




| Screw thread | Length | | Diameter | |
|--------------|--------|--------------------------------|----------|---------------------------------|
| mm | mm | inch | mm | inch |
| R38-R32 | 170 | 6 ³ / ₄ | 55 | 2 ⁵ / ₃₂ |
| T38-R32 | 170 | 6 ³ / ₄ | 55 | 2 ⁵ / ₃₂ |
| T38-R32 | 190 | 7 ¹ / ₂ | 55 | 2 ⁵ / ₃₂ |
| T45-R32 | 185 | 7 ⁹ / ₃₂ | 63 | 2 ³¹ / ₆₄ |
| T45-R32 | 210 | 8 ¹ / ₄ | 63 | 2 ³¹ / ₆₄ |

T45




| Screw thread | Length | | Diameter | |
|--------------|--------|---------------------------------|----------|---------------------------------|
| mm | mm | inch | mm | inch |
| T51-T45 | 218 | 8 ¹⁹ / ₃₂ | 72 | 2 ²⁷ / ₃₂ |

R38



| Screw thread | Length | | Diameter | |
|--------------|--------|-------------------------------|----------|--------------------------------|
| mm | mm | inch | mm | inch |
| T38-R38 | 180 | 7 ¹ / ₈ | 55 | 2 ⁵ / ₃₂ |
| T38-R38 | 190 | 7 ¹ / ₈ | 55 | 2 ⁵ / ₃₂ |


T38



| Screw thread | Length | | Diameter | |
|--------------|--------|---------------------------------|----------|---------------------------------|
| mm | mm | inch | mm | inch |
| T45-T38 | 200 | 8 ¹⁹ / ₃₂ | 63 | 2 ²⁷ / ₃₂ |
| T45-T38 | 200 | 8 | 65 | 2 |


Coupling

R32




| Screw thread | Length | | Diameter | |
|--------------|--------|---------------------------------|----------|--------------------------------|
| | mm | inch | mm | inch |
| T38-R32 | 220 | 8 ¹⁹ / ₃₂ | 55 | 2 ⁵ / ₃₂ |

T45




| Screw thread | Length | | Diameter | |
|--------------|--------|---------------------------------|----------|---------------------------------|
| | mm | inch | mm | inch |
| T51-T45 | 285 | 11 ⁷ / ₃₂ | 72 | 2 ²⁷ / ₃₂ |

T38



| Screw thread | Length | | Diameter | |
|--------------|--------|---------------------------------|----------|---------------------------------|
| | mm | inch | mm | inch |
| R32-T38 | 220 | 8 ¹⁹ / ₃₂ | 45 | 1 ⁴⁹ / ₆₄ |
| T45-T38 | 250 | 9 ²⁷ / ₃₂ | 63 | 2 ³¹ / ₆₄ |
| T51-T38 | 263 | 10 ⁷ / ₁₆ | 72 | 2 ²⁷ / ₃₂ |

T51



| Screw thread | Length | | Diameter | |
|--------------|--------|----------------------------------|----------|---------------------------------|
| | mm | inch | mm | inch |
| T45-T51 | 270 | 10 ⁴¹ / ₆₄ | 57 | 2 ¹ / ₄ |
| T60-T52 | 500 | 20 | 85 | 3 ¹¹ / ₃₂ |
| T5-T60 | 440 | 17 | 72 | 2 ²⁷ / ₃₂ |